

i Poster

ALL NEW DIGITAL POSTER

Indoor series: P2.5/P1.9





Thickness: 35mm

5mm ultra slim edge design

Whole front maintenance

Aluminum integrated frame

Hidden auto-closing inclined blacket

Frame size: 572 x 1902mm

Display size: 560 x 1890mm

Module size: 280 x 210mm

• Pixel pitch: 2.5mm, 1.9mm

• Display mode: synchronized / asynchronous system

• Signal output: Network cable(RJ45)

• Cross-platform operation: Windows/IOS/Android

Control pattern: network/WIFI/3G/USB

Brightness: P2.5(1200~1500nit); P1.9(1000nit)

Super light design, weight: 32kg/set



HD image quality

- 2.5mm/1.9mm HD image quality
- Refresh rate up to 3840Hz
- Brightness at 1500nits, 3 times brighter than LCD display
- 160° view angle
- High color reproduction
- Compared with indoor LCD poster, with high brightness, super thin & lowpower consumption, iposter is also suitable for bright occasion

synchronized / asynchronous system Plug and play, Cross-platform operation

- Free play at anytime, anywhere
- Real time play by connecting to network
- The screen can be controlled with fixed or portable Windows, IOS & Android devices
- The content can be refreshed and stored in built-in media player through WIFI or USB to achieve asynchronous play



572mm

Networking integrated management

- Play the video by connecting to HDMI, USB or cable
- Multi-screen cascade, unified playing and management
- After networking, it can push notification and control displays worldwide













Multi-screen mode

Stand-alone mode

Multi-screen cascade

Multi-installation

• Suitable for lifting, wall-mounted, floor-standing and creative installation like inclined strut installation







Tilted installation



Floor-standing lifting

Creative tilted installation

Multi-application

Applied in shopping mall, meeting room, control center, airport, station, super market, canteen and restaurant. Can be used as:

- Advertising platform
- Shopping guide information, supporting service information release
- Urgent information, instant message release
- Publicity platform, brand model window







Multi screen assembly 16:9

Package & delivery

- Oxford cloth and reflective tape:
 Applicable in small amount displays and short distance delivery
- Wooden case:
 - Applicable in fixed installation and long or short distance delivery
- Flight case:
 - Applicable for rental display and long or short distance delivery







Edition No: TRT-MKT-2017/10/13

	iPoster		
	0500.	Indoor series	
	MODEL	P 2.5	P 1.9
LAMP	LED Type	SMD(2020)	SMD(1010)
MODULE	Pixel pitch	2.5mm	1.944mm
	LED module size	210×280mm	210×280mm
	Resolution(H×W)	84×112	108×144
	LED driving method	1/28 dynamic scan	1/27 dynamic scan
CABINET	LED module layout(H×W)	9×2	9×2
	Resolution(H×W)	756×224	972×288
	Display area	1.06m²	1.06m²
	Cabinet size	1902×572×35mm	1902×572×35mm
	Net. weight/set	32kg	32kg
	Ingress Protection	Front IP40/Rear IP40	Front IP40/Rear IP40
	Power	AC 240/100±10%	AC 240/100±10%
	Serviceability	Front service	Front service
DISPLAY	Max.Power consumption	600W	750W
	Avg.Power consumption	200W	250W
	Viewing Angle(H/V)	160°/160°	160°/160°
	Brightness	1200~1500cd/m²	1000cd/m ²
	Pixel density(pixel/cabinet)	169,344	279,936
	Contrast ratio	4,000:1	4,000:1
	Temperature/ Humidity (Operation/Storage)	-10°C to +40°C; 10% to 90%	-10°C to +40°C; 10% to 90%
	Lifetime(50% brightness)	80,000hours	80,000hours
	Processing	16bit	16bit
	Colors	281trillion	281trillion
	Refresh rate	≥2880Hz	≥2880Hz
	Frame rate	60fps	60fps
	Brightness level	Manually/Auto/Programmable	Manually/Auto/Programmable

Reserve the right to change the specifications without prior notice.

DISTRIBUIDOR OFICIAL



ATLANTIC DEVICES - POST PRINT S.L.

c/ Pensamiento, 27 Esc. Izq. 3ero 3era (Cuzco) 28020 MADRID Tel. 902 09 06 63

Carrer Innovació, 2 - Bloc 1 Nau 1 (P.I. Les Gavarreres) 08711 Òdena - BARCELONA Tel. 93 804 07 02

info@atlanticdevices.com http://www.atlanticdevices.com